

# Pulling eye

**Weight:** 0.00kg

**Dimensions:** 0.00cm x 0.00cm x 0.00cm

## Description

The **Pulling Eye** is designed to provide a functional and safe way of tensioning down guys at the anchor location. It provides a working load of 3,000 lbs with a 5:1 ratio safety factor (Ultimate strength of 15,000 lbs).

## Features

- Facilitates safe, fast installation of all dead-ends by a pulling point at the anchor
- Installs around the anchor hardware in seconds
- Nodular Iron housing and keeper with EHS steel bolt and nut
- Corrosion resistant powder coating iron
- Accommodates anchor rods from 1/2" - 1-1/4" (12.7 - 31.75 mm)
- Reusable
- Lightweight

## Documentation

### Application Procedures

[SP-2013 \(Pulling Eye\)](#)

## Catalog Pages

[Pulling Eye - Catalog](#)

## Sales Materials

[Pulling Eye - Sell Sheet](#)

## Part Tables

| Catalog Number | Description | Std. Ctn. |
|----------------|-------------|-----------|
| PE-0300        | Pulling Eye | 4 Units   |

## Replacement Parts

| Catalog Number   | Description         | Std. Ctn.   |
|--|---------------------|-------------|
| PE-A-0002  | Pulling Eye: Keeper | As Required |
| PE-B-2019  | Pulling Eye: Bolt   | As Required |
| PE-C-0607  | Pulling Eye: Nut    | As Required |
| Note: 3,000 lb. working load is based on a 5 to 1 safety factor. |                     |             |