

Strand Splice

Strand Splice

PREFORMED™ Strand Splices are used to repair strand or messenger simply and economically. All applications can be checked visually — no guesswork involved. Because of its superior design, the Strand Splice provides maximum strength and excellent fatigue characteristics resulting in longer life for both strand and messenger.



Galvanized Steel, C-Coat								
Catalog Number	Size	Strand Construction	Mean Diameter	Length	No. of Subsets	Color Code	Units Per Carton	Wt./Lbs. Per Carton
Utility Grade C-Coat								
GLS-2115	3/16"	7W	.195"	22"	3	Red	100	20
GLS-2117	5/16"	7W	.327"	29"	3	Black	50	26
GLS-2118	3/8"	7W	.360"	34"	3	Orange	50	42
GLS-2119	7/16"	7W	.435"	41"	3	Green	25	37
Extra High Strength C-Coat								
GLS-2102	3/16"	7W	.186"	27"	2	Red	100	30
GLS-2104	1/4"	7W	.240"	35"	2	Yellow	50	34
GLS-2106	5/16"	7W	.312"	42"	3	Black	50	46
GLS-2107	3/8"	7W	.360"	50"	3	Orange	25	38
GLS-2108	7/16"	7W	.435"	56"	3	Green	25	57
GLS-2109	1/2"	7W	.495"	63"	3	Blue	10	34

NOTE: Left hand lay standard

For use on Mischmetal Alloy (AL/ZN) Strand								
Catalog Number	Size	Strand Construction	Mean Diameter	Length	No. of Subsets	Color Code	Units Per Carton	Wt./Lbs. Per Carton
BLS-9102	3/16"	7W	.186"	27"	2	Red	100	30
BLS-9104	1/4"	7W	.240"	35"	2	Yellow	50	34
BLS-9106	5/16"	7W	.312"	42"	3	Black	50	46
BLS-9107	3/8"	7W	.360"	50"	3	Orange	25	38
BLS-9108	7/16"	7W	.435"	56"	3	Green	25	57
BLS-9109	1/2"	7W	.495"	63"	3	Blue	10	34

NOTE: Left hand lay standard

PLP mischmetal formed wire products are acceptable for use with Bezinal® and Galfan® coated strands.

Bezinal® is a registered trademark of the Bekaert Corporation.

Galfan® is a registered trademark of the Galfan Technology Centre, LLC.