

# Easy Tile Hook Installation Guidelines

## Installing the Easy Tile Hook on a clay or ceramic tile roof

**NOTE:**  
Easy Tile Hooks are to be used only on parallel-to-roof arrays.

Easy Tile Hooks can be attached to the roof using “Decking Attached Fasteners” (see below) and without locating any rafters; however, the decking beneath the substrate must be of adequate thickness for a given type of material. Please consult a local engineer or fastener manufacturer for additional guidance if needed.

These guidelines begin after the mounting locations have been marked for each of the Easy Tile Hooks to be installed. For questions about layout see our publication “Power Rail™ Design Guidelines”.

### Decking Attached Fasteners:

Decking Attachment Fasteners are typically supplied by Preformed Line Products (PLP) with the specific support as a kit. The specific fasteners supplied are RSS™ screws from the GRK Fasteners Company. GRK provides excellent documentation of their fasteners' capacities, including references to ICC-ES™ testing and selection criteria for various decking substrates. PLP provides the RSS screws in the PHEINOX™ configuration with 1/4" diameter. For additional information, please reference:

[http://www.grkfasteners.com/en/selection\\_guide\\_RSS.htm](http://www.grkfasteners.com/en/selection_guide_RSS.htm)

Each Easy Tile Hook kit includes the following items. If any items are missing, call us toll free at 800-260-3792.

Qty	Description
1	Easy Tile Hook with pre-applied butyl mastic
8	1/4" x 2" RSS PHEINOX stainless steel screws (longer screws available when specified)
8	1/4" Neoprene bonded stainless steel washers




Figure 1: Easy Tile Hook Dimensions

## Preparing and Attaching the Easy Tile Hook to Substrate

Installing the Easy Tile Hook requires the removal of tile to access the roof substrate. The Easy Tile Hook is secured to the roof substrate with eight fasteners and sealed via a butyl mastic seal.

- A. Remove the tile.
- B. Peel off protective paper from bottom of Easy Tile Hook, exposing butyl mastic sealant.
- C. Align Easy Tile Hook with pre-determined mounting point and press it firmly to stick to roof.
- D. Install the neoprene bonded washers onto the RSS *PHEINOX* screws with the rubber side down.
- E. Drive the RSS *PHEINOX* screws into the substrate until the neoprene rubber protrudes from the washer edges.
- F. Replace tile.




Figure 2: Remove Protective Paper





Figure 3: Attaching Easy Tile Hook to Roof Substrate



*Figure 4: Installed Easy Tile Hook*



---

Albuquerque Office  
1700 Louisiana Blvd., Suite 130  
Albuquerque, NM 87110

Corporate Headquarters  
660 Beta Drive  
Mayfield Village, OH 44143

Telephone: 800.260.3792  
Fax: 505.889.3548  
[www.preformed.com](http://www.preformed.com)  
E-mail: [info@plpsolar.com](mailto:info@plpsolar.com)

---

© 2017 Preformed Line Products  
PCN 060111-1 Version 1, Rev B  
SP3432