





# Tangent Side Ties: Plastic

**For use on:  
Plastic Jacketed Conductor**

**F-Neck Interchangeable  
Headstyle Insulators**

**ANSI 55-4 Pin  
ANSI 55-5 Pin  
ANSI 57-1 Post  
ANSI 57-2 Post  
ANSI 57-3 Post**

**2-7/8"  
Neck Diameter**



PVC Plastic Ties Catalog Number	Semi-Con Plastic Ties Catalog Number	OD Range (in.)		Nominal Conductor Size	Units per carton	Approx. Wt./Lbs.	Approx. Applied Length (in.)	Insulator Color ID Mark (PVC/SC)	Conductor Color Code (PVC/SC)
		Min.	Max.						
SSF-2250	SSF-2250SC	0.296	0.400	#4, 6/1, 2/64s	50	12	18	Yellow	White
SSF-2251	SSF-2251SC	0.401	0.540	#2, 6/1, 3/64s #4, 7W, 8/64s	50	12	17	Yellow	Green
SSF-2252	SSF-2252SC	0.541	0.730	1/0, 6/1, 10/64s 3/0, 6/1, 4/64s	50	13	17	Yellow	Blue
SSF-2253	SSF-2253SC	0.731	0.920	4/0, 6/1, 10/64s 336.4, 18/1, 6/64s	50	14	19	Yellow	Orange
SSF-2254	SSF-2254SC	0.921	1.100	336.4, 18/1, 10/64s 447, 19W, 8/64s	50	15	20	Yellow	Red
SSF-2255	SSF-2255SC	1.101	1.300	477, 37W, 10/64s 397.5, 19W, 12/64s	50	17	22	Yellow	Black/None

Determine exact Conductor OD over the jacket for correct tie selection.

**EXPLANATORY NOTES:**

- (1) Nominal Conductor size indicates one of various conductors within each range.
- (2) For quantities less than 25 pieces, consult PLP.