# CUSHION-GRIP® Twin Spacer

## GENERAL INFORMATION

The CUSHION-GRIP Twin Spacer is simple to install and is shipped fully assembled (no loose parts).

The break-away bolt provides a clear indication that the proper installation torque has been achieved (no special tools required).

Conductor Spacing is 18 inches (457 mm), but also available in 13 inch (330 mm) spacing.

| Catalog Number | Diameter Range | |
|---|---|---|
| | Min. | Max. |
| CGTS-0101 | 0.673 | 0.713 |
| CGTS-0102 | 0.714 | 0.752 |
| CGTS-0103 | 0.753 | 0.791 |
| CGTS-0104 | 0.792 | 0.831 |
| CGTS-0105 | 0.832 | 0.870 |
| CGTS-0106 | 0.871 | 0.909 |
| CGTS-0107 | 0.910 | 0.949 |
| CGTS-0108 | 0.950 | 0.988 |
| CGTS-0109 | 0.989 | 1.028 |
| CGTS-0110 | 1.029 | 1.067 |
| CGTS-0111 | 1.068 | 1.106 |
| CGTS-0112 | 1.107 | 1.146 |
| CGTS-0113 | 1.147 | 1.185 |
| CGTS-0114 | 1.186 | 1.224 |
| CGTS-0115 | 1.225 | 1.264 |
| CGTS-0116 | 1.265 | 1.303 |
| CGTS-0117 | 1.304 | 1.345 |
| CGTS-0118 | 1.346 | 1.382 |
| CGTS-0119 | 1.383 | 1.421 |
| CGTS-0120 | 1.422 | 1.461 |
| CGTS-0121 | 1.462 | 1.500 |
| CGTS-0122 | 1.501 | 1.539 |
| CGTS-0123 | 1.540 | 1.579 |
| CGTS-0124 | 1.580 | 1.618 |
| CGTS-0125 | 1.619 | 1.657 |
| CGTS-0126 | 1.658 | 1.697 |
| CGTS-0127 | 1.698 | 1.736 |
| CGTS-0128 | 1.737 | 1.776 |
| CGTS-0129 | 1.777 | 1.821 |

**Thermal Rating**
**Standard 125°C**
**HT Version 200°C**

Two versions of the CUSHION-GRIP Twin Spacer are available. The standard version is designed for up to 125°C; 150° for 2 hour emergency conductor operation and the high temperature (HT) version can be used for applications with conductor operating temperatures up to 200°C; 225° for 2 hour emergency.

**Notes:**
For high temperature (HT) version add HT to the catalog number (Example: CGTS - 0112HT).

For 13 inch spacing add -13 to catalog number (Example: CGTS - 0112 - 13 or CGTS - 0112HT - 13 High Temperature version).

| CUSHION-GRIP Twin Spacer for T2 or VR conductors | |
|---|---|
| **Catalog Number** | **Conductor Size** |
| CGTS-T2266 | Partridge |
| CGTS-T2336 | Linnet |
| CGTS-T2397 | Ibis |
| CGTS-T2477 | Hawk |

For 13 inch spacing add -13 to catalog number (Example: CGTS - T2266 - 13).



(440) 461-5200 • inquiries@preformed.com • www.preformed.com