

# Galvanized Steel Extra High-Strength Strand (left-hand lay)

Catalog Number 0" Take-Up	Catalog Number 18" Take-Up	Nominal Strand Range		Nominal Strand Size	Construction	U-Bolt Diameter	Rods Per Set	Rod Length	Subset	Color Code	Rated Holding Strength	Design
		Min.	Max.									
N/A	VG-18-2100	.438	.438	7/16"	7W	5/8"	11	27"	3-4-4	Red	20,800#	Std
N/A	VG-18-2101	.459	.500	1/2"	7W or 19W	5/8"	12	30"	3-3-3-3	Blue	26,900#	Std
VG-0-2108	VG-18-2108	.559	.563	9/16"	7W or 19W	3/4"	11	28"	3-4-4	Yellow	35,000#	Std
VG-0-2102	VG-18-2102	.621	.625	5/8"	7W or 19W	3/4"	11	31"	3-4-4	Black	42,400#	Std
VG-0-2103BR	VG-18-2103BR	0.744	0.754	3/4"	19W	1"	13	44"	3-3-3-3	Yellow	58,300#	Gen2
VG-0-2104BR	VG-18-2104BR	0.878	0.888	7/8"	19W	1"	12	49"	3-3-3-3	Green	79,700#	Gen2
VG-0-2105BR	VG-18-2105BR	1	1.01	1"	19W or 37W	1-1/8"	14	66"	3-3-4-4	Green	104,500#	Gen2
VG-0-2106BR	VG-18-2106BR	1.125	1.125	1-1/8"	37W	1-1/8"	14	95"	3-3-4-4	Purple	130,800#	Gen2
VG-0-2107	VG-18-2107	1.250	1.250	1-1/4"	37W	1-1/2"	16	103"	4-4-4-4	Red	162,200#	Std