

## Galvanized Steel Bridge Strand (left-hand lay)

Catalog Number 0" Take-Up	Catalog Number 18" Take-Up	Nominal Strand Range		Nominal Strand Size	Construction	U-Bolt Diameter	Rods Per Set	Rod Length	Subset	Color Code	Rated Holding Strength	Design
		Min.	Max.									
VG-0-2103BR	VG-18-2103BR	0.75	0.75	3/4"	1x19	1"	12	44"	3-3-3-3	Orange	68,000#	Gen2
VG-0-4104BR	VG-18-4104BR	.813	.813	13/16"	1 x 19	1"	12	54"	3-3-3-3	Red	80,000#	Gen2
VG-0-2104BR	VG-18-2104BR	0.875	0.875	7/8"	1 x 19	1"	13	58"	3-3-3-4	Green	92,000#	Gen2
VG-0-4106BR	VG-18-4106BR	.938	.938	15/16"	1 x 31 or 37W	1-1/8"	14	63"	3-3-4-4	Black	108,000#	Gen2
VG-0-2105BR	VG-18-2105BR	1.000	1.000	1"	1 x 31	1-1/8"	14	66"	3-3-4-4	Blue	122,000#	Gen2
VG-0-4108BR	VG-18-4108BR	1.063	1.063	1-1/16"	1 x 31	1-1/8"	14	91"	3-3-4-4	Green	138,000#	Gen2
VG-0-2106BR	VG-18-2106BR	1.125	1.125	1-1/8"	37W	1-1/8"	14	95"	3-3-4-4	Purple	156,000#	Gen2
VG-0-4109	VG-18-4109	1.187	1.187	1-3/16"	1 x 37	1-1/2"	15	99"	3-4-4-4	Orange	172,000#	Std
VG-0-2107	VG-18-2107	1.250	1.250	1-1/4"	1 x 43	1-1/2"	16	103"	4-4-4-4	Red	192,000#	Std
VG-0-4110	VG-18-4110	1.313	1.313	1-5/16"	1 x 43	1-1/2"	17	107"	3-3-3-3-3-2	Black	212,000#	Std
VG-0-4111	VG-18-4111	1.375	1.375	1-3/8"	1 x 43	1-1/2"	17	110"	3-3-3-3-3-2	Orange	232,000#	Std
VG-0-4112	VG-18-4112	1.438	1.438	1-7/16"	1 x 43	1-1/2"	18	114"	3-3-3-3-3-3	Green	252,000#	Std
VG-0-4113	VG-18-4113	1.500	1.500	1-1/2"	1 x 43	1-1/2"	16	119"	3-3-3-3-2-2	Pink	276,000#	Std