




Open Wire Dead-end

Open Wire Dead-ends

PREFORMED™ Dead-ends for Open Wire are designed to be applied by hand in seconds without tools. They exert uniform, positive, gentle gripping. Holding power extends throughout their full length and prevents the concentration of stress points that cause premature line failure. Trim and modern in appearance, they are made of the same material as the conductor to which they are applied and are performance proven even under various climate extremes.



Catalog Number	Wire Gauge	Wire Size	Length	Color Code	Units Per Carton	Wt./Lbs. Per Carton
Galvanized Steel						
GDE-2500	BWG-14	.083"	12"	Yellow	100	6
GDE-2501	BWG-12	.109"	12"	Black	100	9
GDE-2503	BWG-10	.134"	14"	Orange	100	15
Aluminum Clad Steel						
2004511	AWG-11	.091"-.095"	11"	Green	100	7
Copper-Clad Steel						
CWDE-5507	AWG-12	.080"-.081"	11"	Green	100	8
CWDE-5508	AWG-11	.091"-.095"	12"	Red	100	9
CWDE-5509	AWG-10	.102"-.104"	12"	Blue	100	12
CWDE-5510	AWG-9	.114"	13"	Orange	100	13
CWDE-5511	AWG-8	.128"	13"	Black	100	16
CWDE-5512	AWG-6	.162"	16"	Green	100	21