FIBERLIGN® Dielectric Damper for ADSS Cable

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Phone: 123456789 - Email: name@yourdomain.com

Description

A special damper, called the **FIBERLIGN Dielectric Damper**, has been developed specifically for application on ADSS cables. It utilizes the same dampening characteristics as the FIBERLIGN Spiral Vibration Damper, plus provides more gentle gripping.

Features

- Lightweight
- Installs by hand or hot stick

Documentation Application Procedures

SP-2130 (FIBERLIGN® Dielectric Damper)

Catalog Pages

FIBERLIGN® Dielectric Damper - Catalog

Part Tables

FIBERLIGN Dielectric Damper for ADSS Cable					
Catalog Number	Cable Diameter Range (inches)	Cable Diameter Range (mm)	Length inches (m)	Units (per carton)	Carton Weight (lbs.)
50502393	.250326	6.3-8.2	49 (1.24)	50	26
50502272	.327461	8.3-11.6	51 (1.30)	50	28
50502274	.462563	11.7-14.3	53 (1.35)	50	30
50509862	.564770	14.3-19.5	65 (1.65)	50	46
50503057	.771876	19.5-22.2	71 (1.80)	25	30
50503576	.877-1.00	22.3-25.3	72 (1.91)	25	35
50503909	1.001-1.25	25.4-30.5	75 (2.29)	25	40

Notes:

 Consult Preformed Line Products for recommendations on the number of dampers required per span.