



Angle Side Ties: Plastic

**For use on:
Plastic Jacketed Conductor**

**F-Neck Interchangeable
Headstyle Insulators**

**ANSI 55-4 Pin
ANSI 55-5 Pin
ANSI 57-1 Post
ANSI 57-2 Post
ANSI 57-3 Post**

**2-7/8"
Neck Diameter**



PVC Plastic Ties Catalog Number	Semi-Con Plastic Ties Catalog Number	OD Range (in.)		Nominal Conductor Size	Units per carton	Approx. Wt./Lbs.	Approx. Applied Length (in.)	Insulator Color ID Mark (PVC/SC)	Conductor Color Code (PVC/SC)
		Min.	Max.						
SSF-2205	SSF-2205SC	0.296	0.400	#4, 6/1, 2/64s	50	12	18	Yellow	White
SSF-2200	SSF-2200SC	0.401	0.540	#2, 6/1, 3/64s #4, 7W, 8/64s	50	12	17	Yellow	Green
SSF-2201	SSF-2201SC	0.541	0.730	1/0, 6/1, 10/64s 3/0, 6/1, 4/64s	50	14	17	Yellow	Blue
SSF-2202	SSF-2202SC	0.731	0.920	4/0, 6/1, 10/64s 336.4, 18/1, 6/64s	50	14	19	Yellow	Orange
SSF-2203	SSF-2203SC	0.921	1.100	336.4, 18/1, 10/64s 447, 19W, 8/64s	50	15	20	Yellow	Red
SSF-2204	SSF-2204SC	1.101	1.300	477, 37W, 10/64s 397.5, 19W 12/64s	50	16	22	Yellow	Black/None

Determine exact Conductor OD over the jacket for correct tie selection.

EXPLANATORY NOTES:

- (1) Nominal Conductor size indicates one of various conductors within each range.
- (2) For quantities less than 25 pieces, consult PLP.